

1) Mode settings, 2) Optical axis receiver, 3) Optical axis emitter, 4) Power indicator, 5) stability, 6) Sn



## Basic features

Approval/Conformity	cULus CE UKCA WEEE
Principle of operation	Photoelectric sensor
Series	R090K
Style	Square Connection 90°

## Display/Operation

Adjuster	6-turn potentiometer Rotary switch 2 positions
Display	Output function- LED yellow Stability - LED green
Setting	Rated switching distance (Sn) Light-on/dark-on

## Electrical connection

Connection	Connector, M8x1, 4-pin
Polarity reversal protected	yes
Short-circuit protection	yes

## Electrical data

No-load current $I_0$ max. at $U_e$	20 mA
Operating voltage $U_b$	10...30 VDC
Rated operating current $I_e$	100 mA
Rated operating voltage $U_e$ DC	24 V
Ready delay $t_v$ max.	300 ms
Ripple max. (% of $U_e$ )	10 %
Switching frequency	1000 Hz
Turn-off delay $t_{off}$ max.	0.5 ms
Turn-on delay $t_{on}$ max.	0.5 ms
Voltage drop $U_d$ max. at $I_e$	2 V

## Environmental conditions

Ambient temperature	-35...55 °C
IP rating	IP67

## Functional safety

MTTF (40 °C) 92 a

## Interface

Switching output PNP normally open/normally closed (NO/NC)

## Material

Housing material PC  
 PBT  
 Material sensing surface PMMA

## Mechanical data

Dimension 10.7 x 43.5 x 19.5 mm  
 Mounting part Screw M3  
 Tightening torque max. 0.5 Nm

## Optical features

Ambient light max. 10000 Lux  
 Beam characteristic Focus, typical at 90 mm  
 Light spot size Ø 4.5 mm at 60 mm  
 Light type LED, red light  
 Principle of optical operation Diffuse sensor, triangulation  
 Special optical feature Background suppression  
 Switching function, optical dark-on/light-on  
 Wave length 660 nm


## Range/Distance

Range 20...350 mm  
 Rated operating distance Sn 350 mm, Adjustable

## Connector Drawings



## Wiring Diagrams (Schematic)



## Opto Symbols

